

## DS-2CE16D9T-AIRAZH



### Key Features

- 2 Megapixel high-performance CMOS
- Turbo HD output, up to 1080P resolution
- 5-50mm vari-focal lens
- True Day/Night
- OSD menu, 3D DNR, Smart IR
- True WDR, up to 120dB
- IP66 weatherproof
- UTC function

### Specification

Model	DS-2CE16D9T-AIRAZH
Parameter	1080p IR Vari-focal Bullet Camera
Camera	
Image Sensor	1/3" Progressive Scan CMOS
Signal System	PAL/NTSC
Effective Pixels	1956(H)*1266(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time	1/25(1/30) s to 1/50,000 s
Lens	5-50mm
Day & Night	ICR
Synchronization	Internal synchronization
WDR	120dB
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 turbo HD output
CVBS Output	1Vp-p Composite Output(75Ω/BNC)
S/N Ratio	More than 62dB
Menu	

Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/ BW/ EXT
White Balance	ATW/ AWC-SET/ Manual
Privacy Mask	On/Off, maximum 8 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Language	English/ Simplified Chinese/ Traditional Chinese
Functions	True WDR, HLC, 3D DNR, Digital zoom, Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
<b>General</b>	
Working Temperature/Humidity	-40 °C – 60 °C (-40 °F – 140 °F) Humidity 90% or less (non-condensing)
Power Supply	AC24V/ DC12V
Power Consumption	Max. 20W
Weather Proof Ratings	IP66
IR Range	120m
Communication	Up the coax Protocol: HIKVISION-C(Coaxitron)
Dimensions	313.5*100.8*107.3mm
Weight	1.7Kg

## Order Model

DS-2CE16D9T-AIRAZH

## Dimension

