

DS-2CE56D1T-IRMM HD1080P Indoor IR Dome Camera


TURBO HD



Key features

- HD1080P Video Output
- Adopt HDTV Technology
- True Day/Night, Smart IR
- Up to 20m IR distance
- OSD menu controlled via UTC

Dimensions



Accessories



Video balun
DS-1H18

Available models

DS-2CE56D1T-IRMM

DS-2CE56D1T-IRMM	
Camera	
Image Sensor	2 MP CMOS Image Sensor
Signal System	PAL / NTSC
Effective Pixels	1930(H)*1088(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/25(1/30) s to 1/50,000 s
Lens	2.8mm, 3.6mm, 6mm optional Angle of View: 105.8°(2.8mm), 84.3°(3.6mm), 55.4°(6mm)
Lens Mount	φ14
Angle Adjustment	Pan: 0 - 350°, Tilt: 0 - 70°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
S / N Ratio	More than 52dB
Menu	
AGC	Support
D/N Mode	Color/ BW/ EXT
White Balance	Auto/ Manual
BLC	Support
Language	English/ Chinese
Function	Digital noise reduction, Mirror
General	
Working Temperature / Humidity	-20 °C - 45 °C (-4 °F - 113 °F) Humidity 90% or less (non-condensing)
Power Supply	12V DC
Power Consumption	Max. 2.5W
IR Range	Up to 20m
Communication	Up the coax Protocol: HIKVISION-C(Coaxitron)
Dimensions	Φ 98 x 65.4 mm (Φ 3.86" x 2.57")
Weight	130 g (0.29 lb)